




**H5-1 / H9-1**

**Marking Machines for Race Tracks and Sports Facilities**



**H5**  
Losail International  
Circuit  
in Doha, Qatar



**H5**  
Olympic stadium  
in Rome, Italy




**H9**  
Silverstone Circuit  
in Silverstone, UK



**H5**  
Olympic stadium  
in Rome, Italy



**H9**  
Nürburgring  
in Nürburg, Germany



**H9**  
Nürburgring  
in Nürburg, Germany

# H5-1 / H9-1

## Marking Machines for Race Tracks and Sports Facilities

	H5-1	H9-1
<b>Technical Data:</b>		
Engine	1-cylinder 200 cm <sup>3</sup> , Honda gasoline engine, air-cooled, 4,0 kW at 3.500 rpm	1-cylinder 390 cm <sup>3</sup> , Honda gasoline engine, air-cooled, 8,4 kW at 3.200 rpm
Drive	manual	hydraulically infinitely adjustable
Air output	up to 360 l/min (2-cylinder compressor)	up to 670 l/min (2-cylinder compressor)
Dimensions (L x W x H)	1.500 x 800 x 1.050 mm	1.650 x 1.050 x 1.220 mm
Weight approx.	130 kg	255 - 285 kg
<b>Application method / Container volume:</b>		
Cold Paints	Airspray (Low Pressure Method) up to 24 l	Airspray (Low Pressure Method) up to 48 l (1 container) or 2 x 24 l (2 container)
<b>Characteristics:</b>		
Vibration isolation for engine/compressor unit	yes	yes
Fixing for marker unit right and left side	yes	yes
Uniform line widths, even in tight bends	yes	yes
Straight-run fixing device for rear wheel in order to maintain direction easily	yes	yes
Material container with manual agitator	-	yes
Pressurised glass bead container	-	yes
Line width (dependent on material and equipment)	5 - 15 cm	10 - 60 cm
<b>Options:</b>		
Line gap electronic	-	electronic
Can be equipped with additional hand spray gun	yes	yes
Use of commercial paint buckets as an insert container	10 l	30 l
Sports facility execution	yes / right	-
Trailer with driver seat	-	yes